



GE Renewal Parts

Use original equipment parts for reliability
PARTS BULLETIN

UNCONTROLLED COPY

See On-Line Master for Current Revision


DRILLING MOTOR MODEL 5GE752RB3A

27-JAN-2014


© 2006 General Electric Company. All rights reserved. The information contained in this publication is the property of General Electric Company and is disclosed in confidence. This publication is intended for use by GE customers solely for purposes of operating and conducting normal running maintenance of purchased or licensed GE products, and it shall not be reproduced, redistributed, retransmitted, translated, abridged, adapted, condensed, revised or otherwise modified, in any form, in whole or in part, or used for any other purpose, without the express written consent of GE. However, if a GE customer ("Customer") requires additional copies of this document or portions thereof for internal use, GE hereby grants to Customer a limited right to reproduce this publication, in whole or in part, and Customer agrees to use such authorized copies ("Copies") solely for its intended purposes. Any Copies made under this limited reproduction right shall contain this notice and any other legal notices appearing in this publication. The Customer shall be responsible for complying with U.S. export control laws with respect to distribution of all Copies.

GE and Customer agree that the information contained herein does not purport to cover all details or variations in GE products or to provide for every possible contingency with installation, operation or maintenance. Should further information be desired or should particular problems arise that are not covered sufficiently for the user's purposes, the matter should be referred to General Electric Company. Any applicable Federal, State or local regulations or company safety or operating rules must take precedence over any information or instructions given in the Technical Documentation. GE has no obligation to keep the material up to date after the original publication.


GENERAL ELECTRIC COMPANY EXPLICITLY DISCLAIMS ALL WARRANTIES OF ACCURACY, MERCHANTABILITY OR FITNESS FOR ANY PURPOSE IN CONNECTION WITH THE TECHNICAL DOCUMENTATION AND USE THEREOF.



Ref. 1
 (Representative Illustration)
 FIG. 1




(Representative Illustration)
FIG. 1 (Cont'd.)




VIEW OF COMM. END

(Representative Illustration)
FIG. 2



VIEW OF PINION END

(Representative Illustration)
FIG. 2 (Cont'd.)



Ref. 59
Brush Holder
(Representative Illustration)
FIG. 3

GE Proprietary and Confidential Information
UNCONTROLLED COPY
DRILLING MOTOR MODEL 5GE752RB3A
See On-Line Master for Current Revision

PB-31101-035B

FIG. NO.	REF. NO.	PART NO.	QTY	DESCRIPTION
1	1	5GE752RB3A	1	DRILLING MOTOR (SEE PB-31101-035)
1	2	41D735773G1	1	ARMATURE ASSEMBLY
1	3	41C636928P2	1	SHAFT WITH PLUG
1	4	41B537889G1	1	COMMUTATOR (FOR SUPPLY - USE 84B537889G2)
1	5	189V584P1	1	NUT
1	5A	41D735370G5	1	ARMATURE REWIND KIT
1	6	41A232821P1	1	SLEEVE
1	7	2766829ADP24	AR	BALANCE WEIGHT, 13 IN OD
1	8	2766829ADP26	AR	BALANCE WEIGHT, 14 3/4 IN OD
1	9	84A204808P1	1	SET SCREW, OVAL POINT, 0.375 IN-24
1	10	3X8717	AR	ADHESIVE PUTTY, 8 OZ CAN W/BRUSH APPLICATOR
1	10A	84B530329G3	1	ARMATURE CORE STACK
1	11	41C635865G2	1	FRAME HEAD ASSEMBLY
1	12	481A560G1	1	FLASH RING
1	13	N22P29020B13	6	BOLT, HEX HD, 1/2 IN-13, 1 1/4 IN LONG
1	14	N509P2516B	1	DOWEL PIN, 1/4 IN, 1 IN LONG
1	16	334B761P1	1	BEARING CAP
1	17	8864951P119	1	ROLLER BEARING
1	18	8820219P1	1	BEARING RETAINING NUT
1	19	41A239107P1	2	SCREW, HEX SOC HD, 1/2 IN-13, 3/4 IN LONG
1	20	4732368P1	2	GASKET, 0.021 IN THK
1	21	6739891P2	1	BEARING CAP
1	22	41B537660P9	8	WASHER, FLAT, 0.725 IN ID, 1 IN OD
1	23	N22P33048B13	8	BOLT, HEX HD, 5/8 IN-11, 3 IN LONG
1	24	N5700P21	2	PIPE PLUG, SQ HD, SOLID, 1/8 IN
1	25	3X8717	AR	ADHESIVE PUTTY, 8 OZ CAN W/BRUSH APPLICATOR
1	26	41B537963P1	12	CARBON BRUSH
1	27	41B537660P21	11	WASHER, FLAT, 1.063 IN ID, 2 IN OD
1	28	N22P39032	11	BOLT, HEX HD, 1 IN-8, 2 IN LONG
1	29	2739317P2	1	BEARING CAP
1	30	4732351P1	1	SLEEVE, 9 7/32 IN OD
1	31	4732906P1	2	GASKET, 0.021 IN THICK, 15 IN OD
1	32	N22P33056B13	8	BOLT, HEX HD, 5/8 IN-11, 3 1/2 IN LONG
1	33	41B537660P9	8	WASHER, FLAT, 0.725 IN ID, 1 IN OD
1	34	41C637314P1	1	FRAME HEAD
1	35	8864951P167	1	ROLLER BEARING
1	36	4713640P1	1	FLINGER, 8 1/4 IN OD
1	37	6744700P2	1	BEARING CAP, INNER
1	38	N5700P21	2	PIPE PLUG, SQ HD, SOLID, 1/8 IN
1	39	3X8717	AR	ADHESIVE PUTTY, 8 OZ CAN W/BRUSH APPLICATOR
2	40	41C637285G10	2	COIL WITH POLE PIECE, COMMUTATING
2	41	41C637285G7	2	COIL WITH POLE PIECE, COMMUTATING
1,2	42	885483G4	4	COIL WITH POLE PIECE, EXCITING
1,2	43	41B537660P22	24	WASHER, FLAT, 1.313 IN ID, 2.500 IN OD
1,2	44	N22P45060	12	BOLT, HEX HD, 1 1/4 IN-7, 3 3/4 IN LONG
1,2	45	41B538389P172	12	BOLT, HEX HD, 1 1/4 IN-12, 4 IN LONG, NON-MAGNETIC
2	46	8842961G1	3	CABLE ASSEMBLY
2	47	41C637261G1	1	CONNECTION STRAP, INSULATED
2	48	41C637261G2	1	CONNECTION STRAP, INSULATED

GE Proprietary and Confidential Information
UNCONTROLLED COPY
DRILLING MOTOR MODEL 5GE752RB3A
See On-Line Master for Current Revision

PB-31101-035B

FIG. NO.	REF. NO.	PART NO.	QTY	DESCRIPTION
2	49	41A231281P47	7	BRAZING STRIP
2	50	41A230733P4	8	BOLT W/WASHER, SL HX HD, 1/4 IN-20, 1/2 IN LONG
2	51	8809650P1	8	WASHER, CONCAVE, 1/4 IN, SPR STL
2	52	N203P21B13	8	NUT, HEX, 1/4 IN-20
2	53	41A239176P443	AR	SILASTIC PUTTY
2	54	41A239176P133	AR	SILICONE TAPE, 0.015 IN THICK, 1 IN WIDE
2	55	41A239176P18	AR	TAPE, MICA, 0.005 IN THK, 0.750 IN WIDE
2	56	41A239176P487	AR	VARNISH
2	57	41C637261G5	1	CONNECTION STRAP, INSULATED
2	58	41E903759G1	1	MAGNET FRAME
1,2,3	59	41C632667G6	4	BRUSH HOLDER ASSEMBLY
3	60	41B530659G2	12	PRESSURE ARM
3	61	41A231370P2	12	BUSHING, 1.063 IN LONG
3	62	186V831P1	8	SLEEVE
3	63	41A231378P2	4	PIN, 3/8 IN DIA, 6 5/8 IN LONG
3	64	N509P2548	8	PIN, SPRING DOWEL, 1/4 IN DIA, 3 IN LONG
3	65	N509P912B	8	PIN, SPRING DOWEL, 3/32 IN DIA, 3/4 IN LONG
3	66	41A230733P7	8	BOLT W/WASHERS, HEX HD SL, 5/16 IN-18, 3/4 IN LONG
3	67	41A231370P6	16	BUSHING, 0.575 IN LONG
3	68	41B537844G1	12	SPRING SET ASSEMBLY
3	69	41A233880P1	4	PIN, 7 7/16 IN LONG
3	70	41B535754G27	8	BRUSH HOLDER STUD, MOLDED
0	70A	41B535754G28	8	BRUSH HOLDER STUD, MOLDED (0.002 IN OVERSIZE)
0	70B	41B535754G29	8	BRUSH HOLDER STUD, MOLDED (0.004 IN OVERSIZE)
0	70C	41B535754G30	8	BRUSH HOLDER STUD, MOLDED (0.006 IN OVERSIZE)
0	70D	41B535754G31	8	BRUSH HOLDER STUD, MOLDED (0.008 IN OVERSIZE)
3	71	41A330248P1	12	SPRING SEAT
3	72	41A233867G4	12	SPRING SEAT WITH PIN
1	73	2733755P7	4	BRUSH HOLDER SUPPORT
1	74	41B537660P25	4	WASHER, FLAT, 0.968 IN ID, 1.375 IN OD
1	75	N22P37052B13	4	BOLT, HEX HD, 7/8 IN-9, 3 1/4 IN LONG
2	76	41C636243G2	2	CABLE ASSEMBLY
2	77	41B531137G10	1	CABLE ASSEMBLY
2	78	41B531137G7	1	CABLE ASSEMBLY
2	79	41A210359P12	2	FITTING, 45 DEGREE ELBOW, 0.75 IN TUBE
2	80	41D735504G7	1	SHUNT ASSEMBLY
2	81	4713845P1	1	BOLTING PLATE
2	82	N22P27020B13	10	BOLT, HEX HD, 7/16 IN-14, 1 1/4 IN LONG
2	83	N405P44B13	12	LOCKWASHER, 7/16 IN
2	84	41A319329P2	AR	SEALING COMPOUND (A50E176SI)
2	85	N22P27028B13	2	BOLT, HEX HD, 7/16 IN-14, 1 3/4 IN LONG
2	86	41D735504G6	1	CABLE ASSEMBLY
2	87	N22P33028B13	1	BOLT, HEX HD, 5/8 IN-11, 1 3/4 IN LONG
2	88	N213P33B13	2	NUT, JAM, 5/8 IN-11
2	89	N405P47B13	2	LOCKWASHER, 5/8 IN
2	90	N22P33024B13	1	BOLT, HEX HD, 5/8 IN-11, 1 1/2 IN LONG
2	91	481A539P32	2	CABLE BUSHING, 1 7/32 IN ID, RUBBER
2	92	41C637562G1	1	CABLE ASSEMBLY
2	93	41C637562G2	1	CABLE ASSEMBLY

GE Proprietary and Confidential Information
UNCONTROLLED COPY
DRILLING MOTOR MODEL 5GE752RB3A
See On-Line Master for Current Revision

PB-31101-035B

FIG. NO.	REF. NO.	PART NO.	QTY	DESCRIPTION
2	94	499A918ACP3	1	ELBOW, 90 DEGREE, 3/4 IN CONDUIT
2	95	41A306142P2	1	LOCKNUT, 0.75 IN
1	96	N5700P63	5	PIPE PLUG, 0.75 IN, CSK SQ HD
1	97	41A239914G1	1	INSPECTION COVER, HAND HOLE
0	97A	41A239176P334	AR	GASKET, 1/4 IN THK
0	97B	497A806P12	AR	CEMENT
1	98	41A239663P2	4	PLUG
1	99	N22P29016B13	12	BOLT, HEX HD, 1/2 IN-13, 1 IN LONG
1	100	41C636513G1	1	INSPECTION COVER, UPPER
0	100A	497A806P12	AR	CEMENT
0	100B	41A239176P334	AR	GASKET, 1/4 IN THK
1	101	41D732878G4	1	INSPECTION COVER, LOWER
0	101A	41A239176P334	2	GASKET, 1/4 IN THK
0	101B	497A806P12	AR	CEMENT
1	102	N405P45B13	12	LOCKWASHER, 0.50 IN
1	103	41A235078P57	1	STUD, 3/8 IN-16, 1 3/4 IN LONG
1	104	497A806P78	1	THREADLOCKER 271, HIGH STRENGTH
0	105A	493A471P1	1	HUB, 9.120 IN OD, POWER TAKE-OFF

27-JAN-2014